

# Use of Phase Change Materials to Improve the Performance in Direct Cool Refrigerators

Akshata Namjoshi<sup>1</sup>, Yash Gokhale<sup>2</sup>, Kavita Dhanawade<sup>3</sup>

<sup>1,2</sup>*Department of Mechanical Engineering, LokmanyaTilak College Of Engineering, Koparkhairane, Navi Mumbai, Maharashtra (India)*

<sup>1</sup>*akshu13061994@gmail.com*

<sup>2</sup>*yashgokhale2003@rediff.com*

<sup>3</sup>*Asst. professor, Department of Mechanical Engineering, LokmanyaTilak College Of Engineering, Koparkhairane, Navi Mumbai, Maharashtra (India)*

<sup>3</sup>*nikhil\_kd@rediffmail.com*

**ABSTRACT--** Going greener growing better, refrigeration and air conditioning are necessary for life and will continue to expand worldwide. Its impact on environment is huge and also can be used to mitigate environmental issues. One of the crucial and constant research now-a-days is how to improve refrigeration effect at the same time reduce the CO<sub>2</sub> and associated emissions. The main reason of using phase change materials (PCM) is to enhance the coefficient of performance of the system. These phase change materials when installed around the freezer section (evaporator) would help to reduce the overall electrical consumption.

**Keywords:** Domestic refrigerator, COP, Phase Change Material (PCM)

## I. Introduction

There has been reasonable demand now-a-days for the development of greener refrigeration technologies. Rising and fluctuating prices of fuel ultimately give a higher electricity cost. A growing global environmental awareness and the rising costs of energy are driving the demand for the development of sustainable cooling technologies. In INDIA itself cold appliances are responsible for 17% of average domestic electricity use. Worldwide it has been estimated that there are approximately 1 billion domestic refrigerators in use, although the emissions out from the refrigerators have been greatly reduced by using various environmental friendly refrigerants the real grave problem is the emissions let out during generation of electricity. Various eco-friendly refrigerants like R134a have been already replaced but still developing a sustainable refrigeration system is the rising need for hour.

The compressor among the components is the largest electricity consuming device. Approximations suggest that nearly 40% of energy is being consumed by the compressor. Various researches are especially oriented with a view to reduce the electrical consumption of the compressor and at the same time also get the desired refrigeration effect.

Phase change materials (PCMs) are substances with high latent heat content that freeze and melt at a nearly constant temperature, accumulating or releasing large amounts of energy during the process. The use of PCM in domestic refrigerators would be an ideal solution to save energy up to 60%. However the technology of PCM is in the primitive stages as it is uneconomical and requires a lot of analysis. Most of the household refrigerators that have been used are made to load and run above the recommended usage. The market review past 25 years have proven that most of refrigerators have been operated at temperatures above 5 degree Celsius. Usually there are two types of refrigerators in the market namely direct cool refrigerators using the natural convection system of cooling and forced convection systems. Temperature stability is achieved far better in the forced convention system which is frost free.

## II. Literature Reviews

Refrigeration systems form to be one of the essential subjects in the field of mechanical engineering. Conserving energy and at the same time obtain the desired refrigeration effect is the challenging part and need of the hour. These

materials have great potential to reduce the work load acting upon the compressors and save a considerable amount of energy.

Pradip Subramaniam and Chetan Tulapurkar [2,3,4] have conducted experiment upon the actual designing of novel dual based refrigeration systems. The experiment was performed upon a domestic refrigerator by installing the phase change materials. The PCMs were used as thermal storage units. By using these PCMs as thermal storage units a new sub cooling routine system was introduced. The ultimate aim of this experiment was to improve the coefficient of performance and reduce the running time of compressor. With unique designing methods. Pradip Subramaniam and Chetan Tulapurkar designed a new refrigeration cycle with phase change materials as thermal storage units and the overall food quality used in refrigerators was improved. The results obtained by them were promising Pradeep Subramaniam and Chetan Tulapurkar found out that the refrigeration cycle balance was achieved for both during charging and discharging and also the total gas quantity was properly balanced. One good aspect of the test results was that the food temperatures were more stable for fresh food and especially for the freezer section during the on / off cycling. The PCM based refrigerator in comparison to the conventional refrigerator was effective. This means that PCM is effective in bringing down the fluctuations in the fresh food temperature, which is invariably seen in either single or dual evaporator systems without PCM.

Md. Imran Hossen Khan and Hasan M.M. Afroz [5,7] found out that the main problem encountered in domestic refrigerator was of the food quality & weight. The food quality was significantly changed with temp fluctuations due to on-off cycle of compressor. To eliminate the above problem Imran Hossen Khan and Hasan M.M Afroz performed the experiments on domestic refrigerator at different thermal loads to reduce the fluctuations in evaporator cabinet by using two different PCM materials (Water and Eutectic solution (90% H<sub>2</sub>O + 10% NaCl)). As per Md Imran et-al phase change material (PCM) is a latent heat thermal energy storage system which melts and solidifies at a certain temperatures. During the phase change process the material is capable of storing and releasing large amounts of heat energy and that's why it is called as a heat storage system (LHS). The PCM was placed around the five sides of the evaporator cabinet in which the evaporator coil was immersed. The experimental results with PCM confirm the notable reduction of the fluctuation of the cabin temperature at lower load but at higher load this effect is not so encouraging. Between two PCMs, the Eutectic solution was better than water. This reduction of temperature fluctuation ultimately improves the food preservation quality

of the refrigerator. They used PCM material as distilled water and also various Eutectic Solutions. Results obtained were that the use of PCM in a household refrigerator decreases the fluctuations of the cabinet temperatures. By comparing the two PCMs in terms of temperature fluctuations they found out the Eutectic solution is better than water. At higher thermal load this effect is not so encouraging.

Boussinesq [3,4] et-al performed experiments on how to reduce the electrical consumption of a refrigerator system using the phase changing materials. This experiment was conducted on a domestic refrigerator using some ice slabs which were kept in contact with the evaporator section. The results and calculations have proven that the refrigerator could be operated without power supply for a period of 9 to 10 hours. Also in order to compare the isentropic efficiencies the compressor performance for different displacements was also carried out. Further the refrigerator efficiency was calculated. Boussinesq et-al also found out by using the computational fluid dynamics the actual simulations of the airflow inside the refrigerator were determined for both of horizontal and vertical placement of the PCM. The results obtained by them were very conclusive. The CFD model predicted the airflow and temperature distribution within the thermal storage refrigerator. Also a horizontal PCM configuration was found to be more effective than a vertically placed PCM. For the horizontally placed PCM, the CFD predicted temperatures were compared with experimentally measured value and were found to be in close agreement. Both the simulation and the experiments results suggested that a eutectic with a phase change temperature below 0°C would be ideal.

Mahmood Mastani Joybari and Fariborz Haghighi [1] conducted the work of showing numerous of applications of Phase Change Materials especially in the domestic refrigerators. Various advantages and disadvantages were discussed by them. The work conducted by them have concluded that when these phase change materials are kept in direct contact with the naturally cooled evaporator are more effective. However if such a evaporator is being immersed in the phase change material compartment a higher resistance will be created around the evaporator which directly will increase the on off cycle time of the compressor. The phase change material used was water eutectic paraffin having a melting point of 37 degree Celsius. The results were promising but still some modifications are required in the research of PCM refrigeration. The PCM materials were not efficient in condenser because it doesn't give any promising results. By comparing advantages and disadvantages of PCM material installation in evaporator and condenser section has some mutual relation between them.

Rezaur Rahman and Adnan Hasan [5] conducted an experiment for improving the coefficient of performance by installing the phase change materials. In the experiment

performed, around 20-28% COP improvement of the refrigeration cycle was been observed with installing PCM with respect to without PCM. Here the phase change materials were used in chamber built manually and which surrounds the evaporator chamber of refrigerator. So the heat transfer rates in evaporator section increases the performance of refrigerator. The experimental results with PCM confirm that depending upon the thermal load and the type of PCM used, it will show a significant reduction in the compressor running time as compared to the evaporator section without PCM. The material used was distilled water having the known value of latent heat of fusion. The results imposed by them showed that use of water as PCM imposes a great improvement in COP at certain thermal load. For a particular time phase until the PCM melts completely the desired temperature of the product can be maintain during the off cycle of the compressor which ultimately increase the off period of the so it will decrease the energy consumption by refrigerator.

Hence by various such reviews and analysis of the researchers we can conclude that the use of phase changing materials although is challenging yet they are worth useful. Use of such materials is a rising need of the hour. One cannot always depend and believe that energy is available in plenty. There always has to be an alternative for sustaining life and sustaining energy.

### III. The Different Types Of Phase Change Materials

TABLE I  
SALT HYDRATE PCM

Sr no.	Phase changing material	Melting point (°C)	Heat of fusion (KJ/Kg)
1.	Zn(NO <sub>3</sub> ) <sub>2</sub> .6H <sub>2</sub> O (Zinc nitrate hexahydrate)	36.2	246.5
2.	Mn (NO <sub>3</sub> ) <sub>2</sub> .6H <sub>2</sub> O (Manganese nitrate hexahydrate)	25.8	125.9
3.	CaCl <sub>2</sub> .6H <sub>2</sub> O (Calcium chloride hexahydrate)	29.0	190.8

4.	CaBr <sub>2</sub> .6H <sub>2</sub> O (Calcium bromide hexahydrate)	30.2	115.5
5.	LiNO <sub>3</sub> .6H <sub>2</sub> O (Lithium nitrate hexahydrate)	30.0	296
6.	Na <sub>2</sub> SO <sub>4</sub> .10H <sub>2</sub> O (Sodium sulphatedecahydrate)	32.4	254
7.	Na <sub>2</sub> CO <sub>3</sub> .10H <sub>2</sub> O (Sodium carbonate decahydrate)	34.2	146.9
8.	Na <sub>2</sub> HPO <sub>4</sub> .12H <sub>2</sub> O (sodium orthophosphate dodecahydrate)	35.5	265
9.	KF.4H <sub>2</sub> O (Potassium fluoride tetra hydrate )	18.5	231

TABLE II  
ORGANIC PCM'S

Sr.no	Phase change material	Melting point (°C)	Heat of fusion (KJ/Kgk)
1.	CH <sub>3</sub> (CH <sub>2</sub> ) <sub>16</sub> COO(CH <sub>2</sub> ) <sub>3</sub> CH <sub>3</sub> (Butyl stearate)	19	140
2.	CH <sub>3</sub> (CH <sub>2</sub> ) <sub>12</sub> COOC <sub>3</sub> H <sub>7</sub>	19	126
3.	CH <sub>3</sub> (CH <sub>2</sub> ) <sub>12</sub> OH 1-tetradecanol	38	205
4.	CH <sub>3</sub> (CH <sub>2</sub> )(CH <sub>3</sub> ) (Paraffin)	20-60	200

#### IV. Method of selection of PCM materials

4.1 According to thermo-physical properties,  
The melting point of a PCM must be lying in a practical range of operation.

The latent heat should be as high as possible to minimize the physical size of the heat storage.

According to the physical properties, it must have limited changes in density to avoid problems with storage tank, low vapour pressure, favorable phase equilibrium.

4.2 According to chemical properties,

A suitable material should be non-toxic, non-flammable, non-corrosive.

#### V. Experimental Set Up

Experimental setup is shown in fig. 1 having specifications as follows:

Refrigerator is of Whirlpool Company.

- Compressor Model – THK1340
- Refrigerator Gross Capacity – 175lts.
- Power Input – 94w
- Current – 0.8A
- Refrigerant Charge with AMT – 85
- Refrigerant Type – R134a
- Voltage Limit

NORMAL	MINIMUM	MAXIMUM
230V	160V	260V
50HZ		

Refrigerant R-134a

- It is haloalkane refrigerant with thermodynamic properties similar to R-12 but with less ozone depletion potential.
- Its Chemical formula is  $\text{CFH}_2\text{CF}_3$  - Tetrafluorethane
- No chlorine




Fig. 1 Experimental set up

##### A The Main Working Area

The main working area is evaporator section which is shown in the fig 2.




Fig. 2 Main working Area

#### VI. Procedure

Experiment was performed for one hour. Following is the procedure of the experiment -

- ) Switch on the main switch.
- ) Let the stable conditions of the refrigerator be achieved
- ) Then after one hour take the temperature and pressure readings.
- ) Then calculate the COP of the system and note down the energy meter

reading and do the power consumption calculations without PCM materials.

Total we were having 500ml of PCM material. So we have divided it in to 4 four parts.

Then carry out the same procedure for all four sets with PCM.

## VII. Methodology

Methodology 1 represents calculating the COP which is shown in fig 3.

And Methodology 2 represents energy consumption & it's cost which is shown in fig 4.




Fig.3 Methodology 1




Fig. 4 Methodology 2

### Calculation of actual COP without PCM

Step 1:

$$\text{Power input} = m \times \text{work input}$$

$$m = \text{Power input} / \text{work input}$$

$$m = 0.1 / (425 - 386)$$

$$m = 2.56 \times 10^{-3} \text{ Kg/sec}$$

Step 2:

$$\text{Refrigerating capacity} = m \times \text{Refrigeration effect}$$

$$\text{R.E.} = (h_1 - h_4)$$

$$\text{R.E.} = 130 \text{ KJ/Kg}$$

$$\text{Refrigeration capacity} = 2.56 \times 10^{-3} \times 130$$

$$\text{R.C.} = 0.333 \text{ kw}$$

$$Q = 0.0946 \text{ TR}$$

Step 3:

$$\text{Actual COP} = 3.5 \times Q / m \times c_{p,x} (T_{\text{max}} - T_{\text{min}})$$

$$\text{Actual COP} = 2.40$$

### Power Consumption & its cost per month without PCM

$$\text{Power consumed in one hour} = 0.1 \text{ kw}$$

$$\text{Power consumed in one day} = 0.1 \times 24$$

$$= 2.4 \text{ kwh/day}$$

$$\text{Power consumed per month} = 2.4 \times 30$$

$$= 72 \text{ kwh/month}$$

Now,

If we consider Rs3 cost for 1kw-hr (kwh)

$$\text{Electricity cost per day} = 2.4 \times 3$$

$$\text{Electricity cost per day} = 7.2 \text{ Rs}$$

$$\text{Electricity Cost per month} = 7.2 \times 30$$

$$\text{Electricity Cost per month} = \text{Rs } 216$$

### Calculation of actual COP for 125ml phase change material

Observation table for compressor ON-OFF period

SR.NO.	TIME	COMPRESSOR ON (MIN)	COMPRESSOR OFF (MIN)
1.	12:48 PM - 01:11 PM	23:00	—
2.	01:11 PM - 01:41 PM	—	30:00

Experiment was carried for 1 hour [60min]

Calculations:

$$P_c = 145 \text{ psi}, T_c = 50^\circ\text{C}$$

$$P_e = 1.22 \text{ bar}, T_e = -4.1^\circ\text{C}$$

Step 1:

$$\text{Power input} = m \times \text{work input}$$

$$m = \text{Power input} / \text{work input}$$

where,

$$W1 = (h_2 - h_1) = (425 - 386) = 39 \text{ KJ/kg}$$

$$m = 0.075/39$$

$$m = 1.9234 \times 10^{-3} \text{ kg/sec}$$

Step 2:

$$\text{Refrigerating capacity} = m \times \text{Refrigeration effect}$$

$$R.E. = (h_1 - h_4)$$

$$R.E. = 130 \text{ KJ/Kg}$$

$$\text{Refrigeration capacity} = 1.92 \times 10^{-3} \times 130$$

$$R.C. = 0.25 \text{ kw}$$

$$Q = 0.071075 \text{ TR}$$

Step 3:

$$\text{Actual COP} = 3.5 \times Q / m \times c_{p,x} (T_{\text{max}} - T_{\text{min}})$$

$$\text{Actual COP} = 2.40$$

### Power Consumption & its cost per month with PCM

$$\text{Power consumed in one hour} = 0.075 \text{ kw}$$

$$\text{Power consumed in one day} = 0.075 \times 24$$

$$= 1.8 \text{ kwh/day}$$

$$\text{Power consumed per month} = 1.8 \times 30 = 54 \text{ kwh/month}$$

Now, If we consider Rs3 cost for 1kw-hr (kwh)

$$\text{Electricity cost per day} = 1.8 \times 3$$

$$\text{Electricity cost per day} = 5.4 \text{ Rs}$$

$$\text{Electricity Cost per month} = 5.4 \times 30$$

$$\text{Electricity Cost per month} = \text{Rs}162$$

### VIII. COP (Coefficient Of Performance)

Calculation of COP and calculation of efficiency depends upon the required output. |

If the required output is in the form of heat then we need to calculate COP |

In case of Refrigerators and AC systems the output is always in the form of heat and hence COP. |

Higher the value of COP lower is its operating cost. ||

$$\text{COP} = \frac{\text{Refrigeration effect}}{\text{Work input}}$$

### IX. Results

Ideal COP without PCM is 4.99

Theoretical COP without PCM is 3.33

Actual COP without PCM is 2.40.

Actual COP with PCM (125ml) is 2.40

## X. Conclusion

Use of phase changing materials is indeed useful and will significantly contribute to society in saving energy. Due to its appreciable thermo physical properties it has various uses. Use of phase change materials will indeed save electricity and also improve the quality of food in terms of hygiene by reducing the fluctuations of temperatures in the evaporator section. It was observed that there is no significant change in COP value but the performance has improved in terms of saving in electricity by using 125 ml PCM material for the refrigerator we have used in our experiment. Bottom-line we can conclude that phase changing materials are indeed useful serving elements in the refrigeration industry.

## XI. References

- [1] M.M. Joybari, M.S. Hatamipour, A. Rahimi, F.G. Modarres, Exergy analysis and optimization of R600a as a replacement of R134a in a domestic refrigerator system, *International Journal of Refrigeration*, 36 (4) (2013) 1233-242.
- [2] Corrosion experiments on Salt Hydrates used as Phase Change Materials in Cold Storage by Luisa F Cabeza , Ferran Badia , Joseph IIIa , Joan Roca for Universitat de Lleida , SPAIN
- [3] Product Information of DOWFROST Inhibited Propylene Glycol based Heat Transfer Fluid from DOW chemicals.
- [4] Website [www.dow.com](http://www.dow.com). Refrigerator with thermal storage US Patent No 6327871B1 by Mr. Alexandar Rafalovich , Eutectic salts thermal & latent heat properties by EPS Limited United Kingdom. . Design and Performance of a household Refrigerator using Phase Change Materials – Based on Thermal Energy Storage by Pankaj Mittal , K.T. Yang , Department of Aerospace and Mechanical Engineering , Indiana published in ASME/JSME Thermal Engineering Conference : Volume 4 in ASME 1995 6. Analysis of Refrigerator / Freezer Appliances having Dual Refrigeration Cycles by Andre Igan , Sandfor A Klein , Douglas T Reindl for ASHRAE Transactions for 2000 edition Volume 106 , Part 2.
- [5] Blond, G., M. Le Meste, (2004) “Principles of frozen storage”, In: Hui, Y.E., Cornillon, P., Legaretta, I.G., Lim, M.H., Murrell, K.D., Nip, W. (Eds.), *Handbook of Frozen Foods*. Marcel Dekker, New York. pp. 25-53. [2] Canet, W., (1989) “Quality and stability of frozen vegetables”, In: Thorne, S. (Ed.), *Developments in Food Preservation*, Elsevier, London, pp. 1–50.
- [6] “Suprabhat A. Mohod, Sachin R Karale (2014) *IJRC, Review on solar water heater with phase change materials*”.
- [7] Subramaniam, P., C. Tulapurkar, R. Thiyagarajan, G. Thangamani, (2010) “Phase change materials for domestic refrigerators to improve food quality and prolong compressor off time”, *Int. Refrigeration and Air Conditioning Conference at Purdue*.
- [8] Simard A.P., Lacroix M., (2003), Study of the thermal behaviour of a latent heat cold storage unit operating under frosting condition. *Energy Convers. Manag.* 44, 1605-1
- [9] Azzouz, K., D. Leducq, J. Guilpart, D. Gobin, (2005) “Improving the energy efficiency of a vapor compression system using a phase change material. In: *Proceedings 2nd Conference on Phase Change Material & Slurry*”, Yverdon les Bains, Switzerland.
- [10] E. Oró, L. Miró, M.M. Farid, V. Martin, L.F. Cabeza, Energy management and CO<sub>2</sub> mitigation using phase change materials (PCM) for thermal energy storage (TES) in cold storage and transport, *International Journal of Refrigeration*, 42 (0) (2014) 26-35.
- [11] EN 153:2006 Methods of measuring the energy consumption of electric mains operated household refrigerators, frozen food storage cabinets, food freezers and their combinations, together with associated characteristics. European Committee for Standardization. 2006.